









QUARTZ CRYSTAL CATALOG

Model	Frequency	Load	Package	Stability @ 25C	Operating Temperature	Page	
	BFC1x5	32.768kHz	8.0pF	20ppm	-10 C° to +60 C°	C3	
	BFC2x6		12.5pF				2x6mm Can
	BFC3x8						3x8mm Can
	B306	32.768kHz	6-32pF/ Series	j-Lead SMD	20ppm	-40C° to +85C°	C4
	B506	3.579545 to 90.0MHz	10pf-32pF/Series	j-Lead SMD	50ppm	-40C° to +85C°	C5
	BFC25	12.0 to 80.0 MHz	9pF, 12pF, or custom	SMD 2.5x2x0.55mm	±10ppm ±30ppm Custom	-10 C° to +60 C° Custom	C6
	BFC32	12.0 to 55.0MHz	10pf-32pF/Series	3.2x2.5x0.7mm	±50ppm, ±30ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -40C° to +85C°	C7
	BFC42	13.0 to 32.0MHz	10pf-32pF/Series	4.0x2.5x0.8mm	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C8
	BFC53	8.0 to 250MHz	10pf-32pF/Series	5.0x3.2x1.0mm	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C9
	BFC64	12.0 to 150.0MHz	10pf-32pF/Series	6x3.5x1.1mm	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C10
	BFC64B	12.0 to 150.0MHz	10pf-32pF/Series	6x3.5x1.1mm	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C11
	BFC75	8.0 MHz to 150.0 MH	10pF to 32pF (18pF Load Standard) or Series Resonan	7x5x1.3 m	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C12
	BFC75L	4.0 MHz to 14.0 MH	7pF to 32pF (18pF Load Standard) or Series Resonan	7x5x1.3 m	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C13

QUARTZ CRYSTAL CATALOG

	BFCxxxx4	3.5 to 70.0MHz	10pf-32pF/Series	HC-49S	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C14
	BFCxxxx4S			HC-49SS			
	BFCxxxx5B	3.5 to 70.0MHz	10-32pF/ Series	4mm/2lead	±100ppm ±50ppm ±30ppm ±20ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C15
	BFCxxxx5C			3.0mm/2lead			
	BFCxxxx5D			5.6mm/4leads			
	BFCxxxx5E			5.6mm/4leads			
	BFCxxxxU1	3.6864 to 225.0MHz	10-32pF/ Series	UM-1	±100ppm ±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C16
	BFCxxxxU5	10.0 to 225.0MHz	10-32pF/ Series	UM-5	±100ppm ±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C17
	BCC09	3.579545 to 40.0MHz	10pf-32pF/Series	3x9mm Can	±50ppm, ±30ppm ±20ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C18
	BCC10	4.0 to 70.0MHz		3x10mm can			
	BFCxxxx1	1.8432 to 200.0MHz	10pf-32pF/Series	HC-49U	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C19
	BFCxxxx2			HC-49T			
Standard Frequencies							C20



BROOKDALE FREQUENCY CONTROLS



800-229-8033 / 631-242-8033 / 631-595-1845 Fax